











- Kits include flexible length, round top, flashing, mortar guard
- Standard kit lengths of 15', 25' and 35'
- Pull-downs stretch and lead the Flexi-Liner down the chimney
- Liner Material Aluminum 3003, 2-ply (0.005" each)
- Maximum Flue Gas Temperature 470°F
- Stretch Ratio 5:1 (approximate)
- Clearances 0" between liner and chimney interior 0" between combustible materials and chimney exterior
- Compatible with Type B gas vent systems
- Lifetime warranty




## CHIMNEY LINER KITS

Model Number	Description	Barcode
3ALK25	3ALK25 3"X25'AL.CHIMNEY LINER	
3ALK35	3ALK35 3"X35'AL. CHIMNEY LINER	
4ALK25	4ALK25 4"X25'AL. CHIMNEY LINER	
4ALK35	4ALK35 4"X35'AL. CHIMNEY LINER	
5ALK25	5ALK25 5"X25'AL. CHIMNEY LINER	
5ALK35	5ALK35 5"X35'AL. CHIMNEY LINER	
6ALK25	6ALK25 6"X25'AL. CHIMNEY LINER	
6ALK35	6ALK35 6"X35'AL. CHIMNEY LINER	



- 10' flexible liner length.
- Includes coupler and fastener package.
- UL-listed.

## CHIMNEY LINER EXTENSIONS

Model Number	Description	Barcode
3ALKE10	3ALKE10 3"X10' CHIMNEY EXTENSION	
4ALKE10	4ALKE10 4"X10' CHIMNEY EXTENSION	
5ALKE10	5ALKE10 5"X10' CHIMNEY EXTENSION	
6ALKE10	6ALKE10 6"X10' CHIMNEY EXTENSION	